



PRINTING TECHNOLOGIES
ENGINEERED IN GERMANY



Hazardous warning labels

MAXIMUM
PERFORMANCE
FOR SMOOTH
PRODUCTION AND
LOGISTICS PROCESSES

Ihr Microplex Partner:

EMEA
APAC
MICROPLEX PRINTWARE AG
Panzerstraße 5, 26316 Varel
Phone: +49 4451 91370
E-Mail: sales@microplex.de
www.microplex.de

AMER
Canada
MICROPLEX PRINTWARE CORPORATION
30300 Solon Industrial Pkwy Suite E, Solon, OH 44139
Phone: +1 440-374-2424
E-Mail: info@microplex-usa.com
www.microplex-usa.com

The brand names referred to are the registered trademarks of the respective companies. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case.
Version 26.07.2021

FIELD OF APPLICATION


- Hazardous materials labeling
- Price labeling
- Logistics, pharmaceuticals
- Batch printing with variable data

HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- GHS-compliant hazardous materials labeling
- Two color printing to ensure higher impact
- Completely trouble-free paper handling
- Print speed up to 150 mm per second
- SAP®- und AS/400-compatible (through PCL5 + JetCAPS as well as LAN-IPDS)
- Compatible with standard laser printers



MAXIMUM PERFORMANCE FOR SMOOTH PRODUCTION AND LOGISTICS PROCESSES



Reliable printing of hazardous warning labels


The interplay of the surface material and adhesive is decisive for the quality and longevity of hazardous goods labels. Liquids, oil, grease, soapsuds, solvents, acids or salt water should not have a negative impact on the labeling or adhesive. This demands the use of advanced materials – and powerful printers capable of handling such materials easily, swiftly and reliably. Thanks to GHS-compliant printing, continuous batch processing and an optimal processing sequence, Microplex logiJET TC8 fulfill such demanding tasks with impressive speed and at a level of quality you can always rely on – even under the most challenging conditions.

- Compliant with GHS / CLP regulations
- BS5609 compliant printing with Microplex materials
- UV-stable, scratch-resistant, water and solvent resistant

Multiple configurations can realise any application

Microplex printers with its Multi Intelligence Controller provides multiple configuration possibilities. Via configuration the printers can be adjusted to nearly any application requirement. More than 30 printer emulations can be selected. Every emulation can be fine tuned. Beside software signals via SNMP and Status-Out also electrical signals can be used to control the printers and establish a real handshake between printer and system.


SAP® **IBM®**
Linux **simple and easy connection**
Microsoft®




- Direct support of SAP® by the HP PCL5c emulation
- No middleware necessary
- No software modification necessary
- Windows driver supports easy to use handling with all Windows versions
- Many other emulations like PRESCRIBE IIe, Epson ESC/P, CODE-V, ...
- Batch printing from roll-to-roll, small foot print - 39 cm x 42 cm
- Fine tuning by „x“- and „y“-adjustment to get perfect register

Robust printing unit with two colors

The logiJET TC8 is a thermal transfer printer that is perfect for industrial tasks. It is equipped with two robust printing modules, which can be equipped with any color. Windows applications are supported by a Windows driver optimized for this system for all modern Windows versions.



The logiJET TC8 can print on any relevant material like paper, PE, PP, etc. in order to fulfill **GHS / CLP regulations** and **BS5609**.



With the logiJET TC8 you can print material with a width of 100 mm up to 222 mm and almost any length. This ensures that all relevant information can be stored in sufficient size on a label. Suitable combinations of labels and ribbons are available for a variety of applications.

A printing unit with two printing modules offers even more advantages:

- Printing on blank material
- Printing black and red in one go
- Reduction of different preprinted labels
- Reduction of storage costs

For smaller formats the logiJET TC8 can also be used for multi-labels production very efficiently.

The logiJET TC8 is successfully in use at these companies for example:

- DOW Chemicals
- Exxon Mobil
- Chevron Corporation
- Sadara Chemical
- Rheinchemie
- Clariant AG
- Lanxess AG



EXTRACT FROM SPECIFICATIONS

Print engine

Print speed up to 150 mm/s
up to 6 inch/s
Print resolution 300 dpi x 300 dpi
Lifetime print head Transfer: up to 50.000 m
Power supply AC 100 - 120,
200 - 240 V, 50/60 Hz
Power consumption 6,0 A
Dimensions (WxDxH in mm) 389 x 420 x 293 mm
Weight 21 kg (w/o options)
Environment temperature 5 - 35°C
Relative humidity 45 - 75 % (rel.,
non-condensing)

Interfaces USB,
Ethernet-Interface
10/100 MBit, bi-directional (TCP/IP)
Optional: RS232, RS422, IEEE 1284
(Centronics)
Memory RAM: 256 MB
Flash: 256 MB
Display Color-Touch-Panel 3.7 inch
(480x242 pixel)

Printable Media

Size 100 - 222 mm width
printable width max.
219 mm
Paper thickness 0,14 mm - 0,25 mm
Thermal transfer ribbon roll diameter max. 78 mm
Core diameter 1 inch / 25,4 mm
Ribbon length max. 450 m
Coated side outside
Ribbon width max. 220 mm

