

# Thermal Printer Family

**MAXIMUM FLEXIBILITY  
FOR SMOOTH  
PRODUCTION  
WITH THERMAL PRINT  
TECHNOLOGY**



**PRINTING TECHNOLOGIES**  
ENGINEERED IN GERMANY




## FIELD OF APPLICATION

- Mobile applications
- Heavy duty printing applications
- Two-color applications
- UHF RFID option available

## HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- Mobile use with 12 V, 24 V, 36 V or 48 V DC
- Compatible with: PCL5, IPDS, ZPL II and many more
- Format widths from 4 inches to 8 inches
- Fast, robust and reliable
- Compact design, optional mounting plate (logiJET TM4, TM8)
- Robust metal case

Your Microplex Partner:



# MAXIMUM FLEXIBILITY FOR SMOOTH PRODUCTION WITH THERMAL PRINT TECHNOLOGY



## The Perfect Fit for any Application

Within the **Microplex Thermal Printer Family** you will find the best printer solution in terms of print width, speed, material handling and size for any application scenario.

### Heavy-Duty Thermal Printer for the Toughest Continuous Loads



- SOLID thermal printer for toughest demands in production 24/7
- Print speed up to 406 mm/s
- Material width from 1 inch up to 10 inch
- High resolution printout with 300 dpi

### Robust Industrial Printers for Production and Logistics



- Robust metal case, easy handling, versatile and reliable
- 300 dpi print resolution
- Up to 150 mm/s print speed
- „Just-in-Time“ printing for production and logistics

### Mobile Thermal Printer



### 2-Color-Thermal

- Mobile and network-independent thermal printing
- Material width from 1 inch up to 8.7 inch
- 2-color thermal transfer printing
- BS5609 compatible

### Print Module



### Tractor-Thermal



### RFID



- The PM-T8 can be flexibly used as a print module in plant construction.
- The SOLID 45ET-2 can be equipped with two different paper sizes.
- RFID option is available for logiJET T4-2, logiJET T6-2, logiJET TM8, PM-T8.

## Multiple Configurations are Possible

Microplex printer with its Multi Intelligence Controller provides multiple configuration possibilities. Via configuration the printers can be adjusted to nearly any application requirement. More than **40 printer emulations** can be selected. Every emulation can be fine tuned. Beside software signals via **SNMP** and **Status-Out** also electrical signals can be used to control the printer and therefore establish a real handshake between printer and system.

- Monitoring and control of the print out via electrical signals with 8 input and 8 output channels (**GPIO / SPS-Control**)
- Monitoring the printer status via **SNMP** (fleet management)
- User friendly configuration via **web panel**
- Modern WLAN interface with all current protocols, security standards and authentication standards (**IEEE 802.1x**)

## Emulations and Barcodes

**Thermal Printer Emulations, i.e.**  
ZPL II, EPL2, IGP/PGL, Datamax, TEC, IER-Command, Intermec Direct Protocol, LDC, LabelPoint, Etimark MP-1220, cab

**Laser Printer Emulations, i.e.**  
PCL5, IGP/PGL, XES, Kyocera Prescribe, Kodescript+, AGFA Reno, LN03+, BULL-MP6090

**Matrix Printer Emulations, i.e.**  
IGP/VGL, Epson FX-80, Ansi Genicom, CODE-V, MT-600, IBM Proprinter, IPDS

**Further Emulations**  
PDF, CUPS-Raster, HPGL, TIFF, Diablo 630, Lineprinter

**Two-Width Codes**  
Codabar, Code39, MSI, Interleaved 2/5, Interleaved 2/5 (3-Stroke Datalogic), Interleaved 2/5 (3-Stroke Matrix)

**Multiple-Width Codes**  
EAN-8, EAN-13, EAN-128, Add-on-Codes, Code 11, Code93, Code 128, UPC-A, UPC-E

**Height-Modulated Codes**  
Postnet, Planet, KIX, Royalbar, USPS One Code

**2D-Barcodes**  
Aztec-Code, PDF 417, Datamatrix, Maxi-Code, USD-5, QR-Code

## Option RFID


**Frequency Range** 865.600-867.600 (ETSI EN 302 208)  
**RF Power** programmable in 15 levels (1dB step) from 9dBm to 23dBm (from 8mW to 200mW) conducted

**Standard Protocols** EPC C1 G2 / ISO18000-6C  
**Features** read/write/verify (void)  
**Registration of Antenna Position** manual, automatic (depending on antenna design)

## Individual Firmware Adaptation

If a „standard“ Microplex printer does not meet the needed requirements to fit into one specific application or should there be any special requests, we are always able to customize our firmware and make the printer work within the application.

- Individual electrical signals (GPIO / SPS-Control)
- Hardware modifications of the printers
- Emulation adaptations to fully support the customers print data
- Adaptation of status messages (Status-Out)



Examples of the integration of mobile Microplex thermal printers in industrial environments.